



CB Core


Reliable, hygienic, user-friendly
bottled water cooler

- Sleek design, durable materials and proven performance for offices, break areas and education sites.
- Convenient and cost-effective dispenser able to satisfy the essential hydration needs.
- Ideal solution for locations where access to the water supply is limited or unavailable.

Bottled Water Cooler
Freestanding



Product features and benefits



Modern and functional design

Easy to install and use, 'plug and play' setup. Just place in a clear space within your workplace or home, then plug directly into a plug socket to use.

Scratch-resistant surfaces featuring an exclusive, nature-inspired texture.

The top-loading design makes it easy to monitor the water level and know when it's time to change the bottle.



Easy Operation

275 mm dispensing height fits various vessels, including reusable bottles.

Generous 510 ml removable drip tray with floater indicator to show when it's full and needs emptying.



Efficient and sustainable technology

Created using recyclable materials to minimize environmental impact.

Featuring the WaterGuard® system to offer protection against water leaks from damaged bottles and to ensure that air-borne pollutants do not enter the reservoir.


Shielded faucets for better hygienic protection.

Cold tank capacity of 2.2 L.

'Inside-out' cooling probe design to ensure a more efficient cooling method by conserving energy, eliminating condensation, and preventing rust formation within the dispenser.



Technical specifications



Water options

Ambient	Cold	Hot
		

Specifications

Model	Cold & ambient
Dimensions	330 mm (W) x 340 mm (D) x 1040 mm (H)
Weight	11.9 kg
Dispense (alcove) height	275 mm
Drip tray capacity	510 ml
Internal waste	No
External waste	No

Technology and performance

Refrigerant gas	R600a
Cooling technology	Removable Reservoir (RR)
Cold tank capacity	2.2 L
Hot tank capacity	N/A
Dispensing capacity (flow rate)	1.9 L/m
Cooling water capacity < 12°C	5.9 L/h*
Target temperature - Cold Water	5 °C
Target temperature - Hot Water	N/A
Max electrical consumption	60 W

Installations requirements

Power supply	230 V/50 /60 Hz
Water supply	Bottle-fed
Mains waste	Not required
Ventilation space	An air gap of 100mm is required

